



OWCdigital.com



Up to 2500MB/s



Rugged MIL-STD810G  
drop test certified



Thunderbolt 3



Mac & Windows

# OWC Envoy Pro EX

Thunderbolt 3

## Rugged Portability in Overdrive

Shift your expectations of speed, performance, capacity, and portability with the Envoy Pro EX family of rugged, bus-powered, lightning-fast external SSDs.

The OWC Envoy Pro EX portable SSD with Thunderbolt 3 provides ultra-fast, production-level storage for audio, design, and photography workflows.

Built in a strong, slim, and stylish aluminum enclosure it's the perfect project drive that provides rugged military-level protection from the drops and bruises demanded of portable drives. Designed to run cool and silent, the OWC Envoy Pro EX is fully bus powered with zero moving parts. It's the perfect portable powerhouse for demanding environments that won't let you down.

## Key Features

- Up to 2,500MB/s blazing fast performance
- High-performance storage for demanding applications
- Couples NVMe SSD and Thunderbolt 3 performance
- Compact and portable design
- Rugged MIL-STD810G drop test certified design<sup>1</sup>
- Protective impact absorbing bumper
- Bus-powered drive (no AC adapter required)
- Integrated Thunderbolt 3 cable
- Thunderbolt Certified for Mac and Windows



# OWC Envoy Pro EX with Thunderbolt 3

## Tech Specs

### Interface

- (1) Thunderbolt 3 captive cable

### System Requirements

- OS Compatibility
  - macOS 10.13 or later
  - Windows 10 or later
- Hardware
  - Any Mac or PC with a native Thunderbolt 3 port
- Boot Requirements
  - Mac: macOS 10.13 or later
  - Windows PC: booting not supported

### Performance

- Read: Up to 2,500MB/s and Write: Up to 800MB/s

### Operating Environment

- Non-Operating
  - Temperature (°F): -40° to 167°
  - Temperature (°C): -40° to 75°
- Operating
  - Temperature (°F): 32° to 158°
  - Temperature (°C): 0° to 70°

### Includes

- OWC Envoy Pro EX with Thunderbolt 3 captive cable
- Removable rugged bumper
- User guide

### Warranty

- 3 Year OWC Limited Warranty

### Drive With Bumper

- 2.9 in (W) x 0.9 in (H) x 5.7 in (D)
- 7.4 cm (W) x 2.3 cm (H) x 14.5 cm (D)

### Drive Without Bumper

- 2.6 in (W) x 0.8 in (H) x 5.6 in (D)
- 6.5 cm (W) x 2.0 cm (H) x 14.3 cm (D)

### Captive Cable Length

- 5.9 in (15.0 cm)

### Drive Weight With Bumper

- 10 oz (0.3 kg)

### Drive Weight Without Bumper

- 9.6 oz (0.3 kg)

### Box Dimensions

- 8.0 in (W) x 4.8 in (H) x 2.5 in (D)
- 20.2 cm (W) x 12.2 cm (H) x 6.4 cm (D)

### Box Weight

- 0.8 lb (0.4 kg)

### Master Carton Dimensions – 20 pieces

- 16.5 in (W) x 10.3 in (H) x 10.4 in (D)
- 41.8 cm (W) x 26.2 cm (H) x 26.3 cm (D)

### Master Carton Weight – 20 pieces

- 10.8 lb (4.9 kg)



PART NUMBER	CAPACITY	UPC	AVAILABLE
OWCTB3ENVP05	480GB	810586031523	now
OWCTB3ENVP10	1TB	810586031530	now
OWCTB3ENVP20	2TB	810586031547	now
OWCTB3ENVP40	4TB	810586035026	now



OWCdigital.com

1. Test performed by a third party testing and certification service. To achieve this level of certification the drive was dropped over 25 times at every angle from a height of four feet.